

**Defcon 5 S.r.l.**

Via Cristans, 24 - 33085 Maniago PN

Tel: +39 0427 739132 Fax: +39 0427 737791

P.Iva: IT-01568980930

Tactical lights**STREAMLIGHT VINTAGE 180****Code: SL-88913****Brand: Stream light**

The new and versatile Vantage 180 X for firefighters is three lights in one! It's a **helmet mounted** light for hands-free tasks, a **right angle light** that can attach to your turnout gear, and a **handheld flashlight**. So wear it, hold it, clip it, or even hang it !

This light is available two ways, the *Vantage 180 X USB* is a complete rechargeable system that includes one Streamlight SL-B26™ protected Li-Ion USB rechargeable battery pack with a micro USB port right in the battery. The *Vantage 180 X* includes two CR123A lithium batteries.

- The light features Multi-Fuel innovation that allows it to accept either one rechargeable Streamlight SL-B26™ protected Li-Ion USB rechargeable battery pack or two CR123A lithium batteries, so you'll always have a beam when you need it
- High and low modes:
 - High for a super-bright spot beam: 250 lumens; 170m beam; runs 5 hours (SL-B26 battery pack); runs 4 hours (CR123A)
 - Low for a less intense beam and longer run time: 100 lumens; 103m beam; runs 15 hours (SL-B26 battery pack); runs 12 hours (CR123A)
- As a helmet light, it fits both traditional and modern style helmets
- Easily attaches above or below helmet brim; no tools necessary to quickly remove for use as a handheld flashlight
- Rear BLUE LED taillight for helmet mount use so you can be seen from behind by your team
- As a right-angle light, it has a forward facing spot light with downcast light
- White LED taillight in right angle mode has a downcast flood light to see what's at your feet (switches from Blue LED)
- Head articulates 180° to aim the beam where you need it
- Push-button switch for easy, one-handed operation
- High-impact, "super-tough" nylon construction
- Integrated stainless steel clip for maximum flexibility
- Turnout gear attachment hook
- IPX7 waterproof to 1m for 30 minutes; 1m impact resistance tested
- Black color
- Dimensions : 5.20 in. (13.20 cm); 5.5 oz. (156g) with batteries; 5.9 oz. (167g) with SL-B26 battery pack

Meets requirements of NFPA 1971-8.6 (2013)

Weight: 100 grams

Weight (Kg): 0.10



Gallery

